





Kupplungsdichtung für TW-Kupplungen



- ☐ Norm : DIN 28450 für die TW-Armatur
- ☐ Material (Standard) : Vu=Vulkollan/Polyurethan, Pe=Perbunan, Vi=Viton, Hy=Hypalon, Ep=EPDM, Si=Silikon, Te=Teflon, Te/Pe=Teflonmantel mit Perbunankern

Bestell-Nr.	Typ/DN	Abmessung			Material	Gewicht ca - g -	Abb.	Preis - €/Stück -
		D	d	S				
dgsd050xxxvu	GSD50	61,5	49	4,8	Vu	8	1	
dgsd050xxxpe					Pe	9	1	
dgsd050xxxvi					Vi	12	1	
dgsd050xxxhy					Hy	11	1	
dgsd050xxxep					Ep	9	1	
dgsd050xxxsi					Si	8	1	
dgsd080xxxvu	GSD80	92	77	6	Vu	15	1	
dgsd080xxxpe					Pe	18	1	
dgsd080xxxvi					Vi	27	1	
dgsd080xxxhy					Hy	23	1	
dgsd080xxxep					Ep	18	1	
dgsd080xxxsi					Si	15	1	

Bestell-Nr.	Typ/DN	Abmessung			Material	Gewicht ca - g -	Abb.	Preis - €/Stück -
		D	d	S				
dtwf050xxxvu	TWF50	61,5	49	4,8	Vu	7	2	
dtwf050xxxpe		61,5	49	4,8	Pe	6	2	
dtwf050xxxvi		61,5	49	4,8	Vi	10	2	
dtwf050xxxhy		61,5	49	4,8	Hy	7	2	
dtwf050xxxte		60,5	49	4,5	Te	11	2	
dtwf050xxtep		61,6	49	4,8	Te/Pe	10	2	
dtwf050xxxep		61,6	49	4,8	Ep	6	2	
dtwf080xxxvu	TWF80	92	77	6	Vu	15	2	
dtwf080xxxpe		92	77	6	Pe	16	2	
dtwf080xxxvi		92	77	6	Vi	21	2	
dtwf080xxxhy		92	77	6	Hy	16	2	
dtwf080xxxte		90	77	5,5	Te	25	2	
dtwf080xxtep		92	77	6	Te/Pe	24	2	
dtwf080xxxep		92	77	6	Ep	16	2	
dtwv050xxxep	TWV50	61,5	-	4,8	Ep	40	3	
dtwv080xxxep	TWV80	92	-	6	Ep	80	3	
dtwo100xxxpe	TWO100	114	100	7	Pe	16	4	
dtwo100xxxvi					Vi	28	4	
dtwo100xxxhy					Hy	20	4	
dtwo100xxxte					Te	26	4	
dtwo100xxtep					Te/Pe	28	4	